



# CETPATCH FH

2917

Non-metallic non-oxiding floor hardener

### **Description:**

Range of CETPATCH FH are supplied as a ready to use factory controlled cementitious system blended with special aggregates selected for high abrasion and wear resistance and additives. Based on non-metallic non oxidizing aggregate used to produce an impact and wear resistant, dust free surface suitable for most heavy-duty area.

#### **Advantages:**

- ➤ Highly impact and abrasion resistance.
- Long lasting wear resistant surface
- > Dry shake on applied over fresh concrete to provide a monolithic bond.
- Ready to use, factory controlled eliminates on site mixing.
- Resists oil and grease penetration and reduces dusting.
- Low maintenance and easy to use.
- Non slip and anti-skid.

### Area of application:

- Engineering work-shops,
- Where houses,
- Production areas,
- Garages,
- Subways
- > Railway platforms
- Loading bays,
- > Ship yards & Utility building

#### **Direction for use:**

- > The base concrete should have a minimum cement of 300 kg/cm2 with a slump of 40-60 mm with low water cement ratio. (can be use CETPROOF CA).
- > The bleeding water should evaporate and CETPATCH FH can be broadcast after initial set.
- > CETPATCH FH is broadcast evenly manually and when the surface darkness with the absorption of water the surface is floated.
- > To apply second application immediate.

Packing: Supplied in 30 kg

**Disclaimer:** The product information & application details given by the company & its agents have been provided only as a general guideline for usage. No guarantee / warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products

## Ashapura Minechem Ltd.

Head Office: Jeevan Udyog Building 3<sup>rd</sup> Floor, 278, D. N. Road, Fort Mumbai -400 001 (India)

Email: info@ashapura.com | www.ashapura.com

Phone: Mumbai +91 22 6665 1700 | Ahmedabad 079 - 40063751 / 4

CIN No.: L14108MH1982PLC026396

