



CETPROOF RMC

1517

Water reducing / Retarding Super Plasticiser

Description:

CETPROOF RMC is based on processed Naphthalene & Ligno sulphonated and additives which is supplied as brown liquid and can be used with all types of Portland cements.

Advantages:

- ❖ Extends setting time.
- ❖ Prevents cold joints in monolithic structure.
- ❖ Increased workability makes places easier compaction and finishing
- ❖ Reduced permeability and increased durability.
- ❖ Reduction in w/c ratio.
- ❖ Used in pump concrete

Area of application:

- Hot weather concreting.
- Ready-mix concreting.
- Congested reinforcement.
- Above or below grade waterproofing.
- For controlled delays to initial and final setting of concrete mixes.

Properties:

- Appearance : Brown liquid
- Specific Gravity : 1.150 to 1.160
- IS Standard : 9103-1779
- ASTM Standard : 494-86 Type D

Direction for use: Add the required dosage to the gauging water

Dosage: 200 g to 600 g per 50 kg cement

Packing: Supplied in 225 kg

Disclaimer: The product information & application details given by the company & its agents have been provided only as a general guideline for usage. No guarantee / warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products

Ashapura Minechem Ltd.

Head Office: Jeevan Udyog Building

3rd Floor, 278, D. N. Road, Fort

Mumbai -400 001 (India)

Email: info@ashapura.com | www.ashapura.com

Phone: Mumbai +91 22 6665 1700 | Ahmedabad 079 – 40063751 / 4

CIN No.: L14108MH1982PLC026396



Ashapura
Group Of Industries
Since 1960