



Polymer based undercoat (UC) Unique 2 in 1 application Plaster-cum-Wall Putty

Cetplast UC is a versatile facing material that can be applied to directly over smooth concrete surface without hacking, or undulating surface and can be used as base coat /undercoat for interiors or as final finish for exteriors.

Cetplast UC is polymer modified White cement based specially 2-in-1 thin application Plaster-cum-Wall Putty in 3 to 6 mm thickness in two coats against conventional plater 12 mm plus Putty 1.5 mm

Advantages:

- Under Coat over plaster or Directly on Concrete surface.
- Excellent Adhesion with substrate
- Reduce water absorption and Crack resistant.
- Superior mat finish, Durable & easy to use.
- Economical 3 to 6 mm thickness against conventional plater 12 mm
- Does not require curing after application.
- Ideal for Internal, External wall surface & Ceiling.
- Available in Light Grey Finish & White finish.

Area of application:

- All type of concrete surface.
- All type of plaster and concrete wall.
- Ceilings
- Inner and outer wall.
- Ideal for heritage buildings repair.

Direction of use:

Surface Preparation:

- The surface should be free from loose particles and any other foreign materials.
- Remove all foreign and loose materials from the wall surface with help of emery stone, putty blade or wire brush and clean the surface with water.

Mixing:

- Mix 25 kg cetplast UC & 6 to 6.5 litres of water to stiff consistency by using suitable mixer.
- Leave the mixture for 5 minutes for polymerisation and remix.
- Use within 90 minutes. Mix the product in such quantities that it can be used in specific time.

Application:

- Apply 1st coat of cetplast UC (3 mm thickness) using a blade/spatula on the wall with bottom to up direction.
- Apply 2nd coat of Cetplast UC (1.5 to 3 mm thickness) after 6 to 8 hours in other direction.
- For better silky finish for interiors wall use 2nd coat cetcoat SF
- Allow complete drying for 3 days.
- Don't use fine emery paper to remove application marks, take care during application to avoid mark.

**Precaution & Safety:**

Cetplast UC Plaster-cum-Wall Putty contains eco-friendly fillers and additives, however being white cement based, it is alkaline and hence it is advisable to avoid direct eye and skin contact. In case of eye contact, flush with clean water at least for 15 minutes and seek medical help if burning continues. It is recommended to keep it out of reach of children.

Coverage:

- 50 to 60 sq. ft. per 25 kg bag for thickness of 3 mm. Although, the coverage area would depend on the surface quality.

Packing:

Supplied in 25 kg Moisture resistant bag.

Disclaimer: The product information & application details given by the company & its agents have been provided only as a general guideline for usage. No guarantee / warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our product.

Ashapura Minechem Ltd.

Head Office: Jeevan Udyog Building

3rd Floor, 278, D. N. Road, Fort

Mumbai -400 001 (India)

Email: info@ashapura.com | www.ashapura.com

Phone: Mumbai +91 22 6665 1700 | Ahmedabad 079 – 40063751 / 4

CIN No.: L14108MH1982PLC026396



Ashapura
Group Of Industries
Since 1960